

Fleetwood Electronic Lock Hardware – Quick Facts

Factory Supplied:

- Fleetwood purchased door configuration
- Electronic multipoint lock with motor drive automation which includes:
 - 45mm backset.
 - 67.25" minimum panel height.
 - Locks are handed (LH or RH) and must be ordered according to Hinge Location (LH or RH).
 - 360 degree profile cylinder standard.
 - Mechanical anti-panic egress (egress is assured with or without power).
 - Control module to manage in/output functions.
 - Magnet contact to sense open/closed position.
 - Cables to connect supplied items.
- Electronic Latch is preprogrammed for 2 modes at time of purchase:
 - Mode 1: latch, deadbolt, and multipoint's stay in the unlocked position (preferred for high traffic situations e.g. parties).
 - Mode 2: all points of contact are in the locked position when the door is shut.
 - Additional modes are available, refer to owners manual at time of purchase.

Additional Supplies Required (NOT PROVIDED BY FLEETWOOD):

- Power supply: 12V DC / 3A min required. See below for reference.
- Entry access system e.g. keypad, biometric or other user interface. The selected device must make a closed contact at the input terminals of the control module for <= 1 sec. to initiate the unlocking sequence.
- Wi-fi or smartphone control must be accommodated via the entry access system you provide. See below for references.

Power Supply Reference:

Supplier	Web	Phone	Product
SE Automation	www.seawi.com	920-380-9400	Siemens: SIEM-6EP13232BA00 SITOP PSU100S 12V/14A, 120/230 VAC, 12V/14A

Entry Access Systems References:

Supplier	Web	Phone
Siedle USA	www.siedleusa.com	800-874-3353
Holovision	http://eholovision.com	714-434-6904