



# Testing Evaluation Laboratories, Inc.

2002 Wood Court Suite 1 – Plant City, FL 33563  
Phone: 813-754-9887

## TEST RESULTS

Dade Lab Certification Number: 11-1213.01  
Test Notification Number: TEL 13-012

Report No: TEL 01991012  
Test Dates: January 16, 2014  
through March 18, 2014  
Report Date: March 21, 2014

### Issued to:

Fleetwood Windows and Doors  
One Fleetwood Way  
Corona, CA 92879

**Project Summary:** Testing Evaluation Laboratories, Inc. (TEL) was contracted by Fleetwood Windows and Doors to perform tests on the 3300 Glacier Sliding Glass Door at TEL's Plant City, FL test facility.

Test specimen descriptions and results are reported herein.

**Test Specifications:** The test specimens were evaluated in accordance with the following:

*High Velocity Hurricane Zone Protocols TAS 202-94, TAS 201-94 and TAS 203-94*

### Test Specimen Description:

<b>Series / Model:</b>	3300 Glacier Sliding Glass Door
<b>Type:</b>	Aluminum Sliding Glass Doors
<b>Overall Size:</b>	240.00" x 120.00" – Specimens 1, 3, 4 and 5 - OXXO 180.00" x 120.00" – Specimens 2 and 6 - OXO 180.00" x 120.00" – Specimens 7 and 8 - OOX
<b>Daylight Opening:</b>	54.75 " x 112.75" – Specimens 1, 3, 4 and 5 (End Panels) 54.63 " x 112.75" – Specimens 1, 3, 4 and 5 (Center Panels) 55.06" x 112.75" – Specimens 2 and 6 (All Panels) 55.06" x 112.75" – Specimens 7 and 8 (All Panels)
<b>Glazing Detail:</b>	Laminated Monolithic Glass – (Specimens 1, 3, 4 and 5) Insulated Laminated Glass – (Specimens 2, 6, 7 and 8) (See attached drawing for details)
<b>Frame Material:</b>	Aluminum
<b>Finish:</b>	Mill Finish

For Tested Elevation, Vertical Cross Sections, Horizontal Cross Sections, Components, Frame Anchoring, Glazing Detail and Bill of Materials See Attached Drawing #L-7112, #L-7113, and #L-7114

**SEQUENCE OF TESTS PERFORMED:**

**STRUCTURAL TESTS (TAS 202)**

**Specimen 1 – 240.0” x 120.0” Aluminum Sliding Glass Door (OXXO)**

**Design Pressure                      Positive 40.0      Negative 40.0**

Air Infiltration (ASTM E283-04)	Pressure 1.57 PSF	SCFM/Ft <sup>2</sup> 0.262	Result Pass
---------------------------------	----------------------	-------------------------------	----------------

**Structural Loads (ASTM E330-02)**

<b>Range</b>	<b>Time (sec)</b>	<b>Load (psf)</b>
Half Test Positive	30	20.00
Design Positive	30	40.00
Half Test Negative	30	20.00
Design Negative	30	40.00

Water Infiltration (ASTM E331-00) Utilizing 2.0” Sill	Pressure 6.00 PSF	Time 15.0 Min.	Result Pass
--	----------------------	-------------------	----------------

Water Infiltration (ASTM E331-00) Utilizing 3.0” Sill	Pressure 8.25 PSF	Time 15.0 Min.	Result Pass
--	----------------------	-------------------	----------------

**Note #1: Water Infiltration performed after Positive and Negative half and design loads.**

**Structural Loads (ASTM E330-02)**

<b>Range</b>	<b>Time (sec)</b>	<b>Load (psf)</b>	<b>Location</b>	<b>Deflection</b>	<b>Set</b>	<b>Allowable (Set)</b>
Half Proof Positive	10	30.00				
Test Positive	30	60.00	1	1.452"	0.000"	0.464"
			2	0.692"	0.027"	0.464"
Half Proof Negative	10	30.00				
Test Negative	30	90.00	1	1.328"	0.016"	0.464"
			2	0.795"	0.053"	0.464"

**Deflection Locations:**

**Deflection/Set for Location 1 measured at center of meeting stiles – Inactive/Active panels and Location 2 measured at center of meeting stiles at latch.**

**Forced Entry**

ASTM F842                      Type "A: Assembly                      Passed

**Conclusion:** TEL observed no signs of failure in any area of this test specimen during the Uniform Static Load Test. In addition, specimen met the permanent set requirements. Therefore, this specimen satisfies the uniform static load test requirements of TAS 202-94.

Jarrett Wright and James Hayhurst, Test Technicians

**SEQUENCE OF TESTS PERFORMED:**

**STRUCTURAL TESTS (TAS 202)**

**Specimen 2 – 180.0” x 120.0” Aluminum Sliding Glass Door (OXO)**

**Design Pressure                      Positive 40.0      Negative 40.0**

Air Infiltration (ASTM E283-04)	Pressure 1.57 PSF	SCFM/Ft <sup>2</sup> 0.207	Result Pass
---------------------------------	----------------------	-------------------------------	----------------

**Structural Loads (ASTM E330-02)**

<b>Range</b>	<b>Time (sec)</b>	<b>Load (psf)</b>
Half Test Positive	30	20.00
Design Positive	30	40.00
Half Test Negative	30	20.00
Design Negative	30	40.00

Water Infiltration (ASTM E331-00) Utilizing 2.0” Sill	Pressure 6.00 PSF	Time 15.0 Min.	Result Pass
--	----------------------	-------------------	----------------

Water Infiltration (ASTM E331-00) Utilizing 3.0” Sill	Pressure 8.25 PSF	Time 15.0 Min.	Result Pass
--	----------------------	-------------------	----------------

**Note #1: Water Infiltration performed after Positive and Negative half and design loads.**

**Structural Loads (ASTM E330-02)**

<b>Range</b>	<b>Time (sec)</b>	<b>Load (psf)</b>	<b>Location</b>	<b>Deflection</b>	<b>Set</b>	<b>Allowable (Set)</b>
Half Proof Positive	10	30.00				
Test Positive	30	60.00	1	1.624"	0.051"	0.464"
			2	2.147"	0.106"	0.464"
Half Proof Negative	10	30.00				
Test Negative	30	90.00	1	1.894"	0.057"	0.464"
			2	2.058"	0.090"	0.464"

**Deflection Locations:**

**Deflection/Set for Location 1 measured at center of meeting stiles at latch and Location 2 Measured at center of meeting stiles, Inactive/Active panels.**

**Forced Entry**

ASTM F842	Type "A: Assembly	Passed
-----------	-------------------	--------

**Conclusion:** TEL observed no signs of failure in any area of this test specimen during the Uniform Static Load Test. In addition, specimen met the permanent set requirements. Therefore, this specimen satisfies the uniform static load test requirements of TAS 202-94.

Jarrett Wright and James Hayhurst, Test Technicians

**SEQUENCE OF TESTS PERFORMED:**

**STRUCTURAL TESTS (TAS 202)**

**Specimen 7 – 180.0” x 120.0” Aluminum Sliding Glass Door (OOX)**

**Design Pressure            Positive 35.0    Negative 35.0**

**Structural Loads (ASTM E330-02)**

<b>Range</b>	<b>Time (sec)</b>	<b>Load (psf)</b>
Half Test Positive	30	17.50
Design Positive	30	35.00
Half Test Negative	30	17.50
Design Negative	30	35.00

**Structural Loads (ASTM E330-02)**

<b>Range</b>	<b>Time (sec)</b>	<b>Load (psf)</b>	<b>Location</b>	<b>Deflection</b>	<b>Set</b>	<b>Allowable (Set)</b>
Half Proof Positive	10	26.25				
Test Positive	30	52.50	1	1.850"	0.179"	0.474"
			2	1.726"	0.039"	0.472"
Half Proof Negative	10	26.25				
Test Negative	30	52.50	1	1.843"	0.083"	0.474"
			2	1.483"	0.017"	0.472"

***Deflection Locations:***

***Deflection/Set for Location 1 measured at center of meeting stiles at latch and Location 2  
Measured at center of meeting stiles, Inactive/Inactive panels.***

**Forced Entry**

ASTM F842            Type "A: Assembly            Passed

**Conclusion:** TEL observed no signs of failure in any area of this test specimen during the Uniform Static Load Test. In addition, specimen met the permanent set requirements. Therefore, this specimen satisfies the uniform static load test requirements of TAS 202-94.

Jarrett Wright and James Hayhurst, Test Technicians

## IMPACT AND CYCLING TESTS (TAS 201/203)

### Specimen 3 – 240.0" x 120.0" Aluminum Sliding Glass Door (OXXO)

#### TAS 201 and 203 – Large Missile Impact (2 x 4 Southern Yellow Pine)

Cond. Temp Of Specimen	Missile Level	Missile Weight	Missile Length	Muzzle Distance From Specimen
76°F	D	9.0 lbs, 1 oz	8'-1/4"	17'1"

Impact Location	Results	X - Measurement	Y - Measurement	Speed
1	Pass	132.0"	11.0"	49.7 fps
2	Pass	154.0"	61.0"	50.1 fps
3	Pass	211.0"	60.5"	50.1 fps
4	Pass	190.0"	10.5"	49.9 fps
5	Pass	182.0"	60.0"	49.9 fps

Orientation of Missile at impact was within +/-5° of horizontal.  
None of the impacts penetrated the specimens.  
"X" measurement is from the left edge of test specimen.  
"Y" measurement is from the bottom edge of test specimen.

#### TAS 201 and 203– Fatigue Load Cycling      Design Pressure +50.0 psf / -50.0 psf

Positive % of Test Load	Positive Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
20% to 50%	10.0 to 25.0	3500	2.46
0% to 60%	0.0 to 30.0	300	2.49
50% to 80%	25.0 to 40.0	600	1.92
30% to 100%*	15.0 to 50.0	100	2.86

Negative % of Test Load	Negative Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
30% to 100%*	15.0 to 50.0	50	2.51
50% to 80%	25.0 to 40.0	1050	1.81
0% to 60%	0.0 to 30.0	50	2.25
20% to 50%	10.0 to 25.0	3350	1.95

\*Panel deflected 2.75" from original plane at 100% Positive load and 4.00" from original plane at 100% Negative load. At the completion of cycles the door panel was operable. There were no tears in the film. In our opinion, the tape and film used to seal for air leakage did not influence the results of the test.

Jarrett Wright and James Hayhurst, Test Technicians

Mfg Observers – Joe Zammit

## IMPACT AND CYCLING TESTS (TAS 201/203)

### Specimen 4 – 240.0" x 120.0" Aluminum Sliding Glass Door (OXXO)

#### TAS 201 and 203 – Large Missile Impact (2 x 4 Southern Yellow Pine)

Cond. Temp Of Specimen	Missile Level	Missile Weight	Missile Length	Muzzle Distance From Specimen
76°F	D	9.0 lbs, 1 oz	8'-1/4"	17'1"

Impact Location	Results	X - Measurement	Y - Measurement	Speed
1	Pass	132.0"	10.5"	49.9 fps
2	Pass	153.75"	61.0"	49.8 fps
3	Pass	211.25"	61.0"	50.0 fps
4	Pass	190.0"	11.0"	49.9 fps
5	Pass	181.75"	60.0"	50.1 fps

Orientation of Missile at Impact was within +/-5° of horizontal.  
None of the impacts penetrated the specimens.  
"X" measurement is from the left edge of test specimen.  
"Y" measurement is from the bottom edge of test specimen.

#### TAS 201 and 203– Fatigue Load Cycling Design Pressure +50.0 psf / -50.0 psf

Positive % of Test Load	Positive Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
20% to 50%	10.0 to 25.0	3500	2.35
0% to 60%	0.0 to 30.0	300	2.24
50% to 80%	25.0 to 40.0	600	2.05
30% to 100%*	15.0 to 50.0	100	2.78

Negative % of Test Load	Negative Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
30% to 100%*	15.0 to 50.0	50	3.00
50% to 80%	25.0 to 40.0	1050	2.06
0% to 60%	0.0 to 30.0	50	2.72
20% to 50%	10.0 to 25.0	3350	2.22

\*Panel deflected 2.75" from original plane at 100% Positive load and 4.13" from original plane at 100% Negative load. At the completion of cycles the door panel was operable. There were no tears in the film. In our opinion, the tape and film used to seal for air leakage did not influence the results of the test.

Jarrett Wright and James Hayhurst, Test Technicians

Mfg Observers – Joe Zammitt

## IMPACT AND CYCLING TESTS (TAS 201/203)

### Specimen 5 – 240.0" x 120.0" Aluminum Sliding Glass Door (OXXO)

#### TAS 201 and 203 – Large Missile Impact (2 x 4 Southern Yellow Pine)

Cond. Temp Of Specimen	Missile Level	Missile Weight	Missile Length	Muzzle Distance From Specimen
76°F	D	9.0 lbs, 1 oz	8'-1/4"	17'1"

Impact Location	Results	X - Measurement	Y - Measurement	Speed
1	Pass	120.50"	54.00"	49.7 fps
2	Pass	154.00"	61.00"	50.1 fps
3	Pass	175.00"	110.00"	49.8 fps
4	Pass	182.00"	62.00"	50.0 fps
5	Pass	210.00"	62.00"	50.1 fps
6	Pass	232.00"	110.00"	49.8 fps

Orientation of Missile at Impact was within +/-5° of horizontal.  
None of the impacts penetrated the specimens.  
"X" measurement is from the left edge of test specimen.  
"Y" measurement is from the bottom edge of test specimen.

#### TAS 201 and 203– Fatigue Load Cycling      Design Pressure +50.0 psf / -50.0 psf

Positive % of Test Load	Positive Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
20% to 50%	10.0 to 25.0	3500	2.44
0% to 60%	0.0 to 30.0	300	2.44
50% to 80%	25.0 to 40.0	600	2.25
30% to 100%*	15.0 to 50.0	100	2.47

Negative % of Test Load	Negative Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
30% to 100%*	15.0 to 50.0	50	2.52
50% to 80%	25.0 to 40.0	1050	2.16
0% to 60%	0.0 to 30.0	50	2.15
20% to 50%	10.0 to 25.0	3350	1.80

\*Panel deflected 2.63" from original plane at 100% Positive load and 3.38" from original plane at 100% Negative load. At the completion of cycles the door panel was operable. There were no tears in the film. In our opinion, the tape and film used to seal for air leakage did not influence the results of the test.

Jarrett Wright and James Hayhurst, Test Technicians

Mfg Observers – Joe Zammit

## IMPACT AND CYCLING TESTS (TAS 201/203)

### Specimen 6 – 180.0" x 120.0" Aluminum Sliding Glass Door (OXO)

#### TAS 201 and 203 – Large Missile Impact (2 x 4 Southern Yellow Pine)

Cond. Temp Of Specimen	Missile Level	Missile Weight	Missile Length	Muzzle Distance From Specimen
74°F	D	9.0 lbs, 3 oz	8'-0"	17'0"

Impact Location	Results	X - Measurement	Y - Measurement	Speed
1	Pass	111.00"	10.00"	50.0 fps
2	Pass	94.00"	61.00"	49.8 fps
3	Pass	121.00"	60.00"	50.1 fps
<p>Orientation of Missile at Impact was within +/-5° of horizontal.                      None of the impacts penetrated the specimens.                      "X" measurement is from the left edge of test specimen.                      "Y" measurement is from the bottom edge of test specimen.</p>				

#### TAS 201 and 203– Fatigue Load Cycling Design Pressure +50.0 psf / -50.0 psf

Positive % of Test Load	Positive Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
20% to 50%	10.0 to 25.0	3500	2.22
0% to 60%	0.0 to 30.0	300	2.15
50% to 80%	25.0 to 40.0	600	2.31
30% to 100%*	15.0 to 50.0	100	2.78

Negative % of Test Load	Negative Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
30% to 100%*	15.0 to 50.0	50	2.93
50% to 80%	25.0 to 40.0	1050	2.52
0% to 60%	0.0 to 30.0	50	2.79
20% to 50%	10.0 to 25.0	3350	2.28

\*Panel deflected 3.00" from original plane at 100% Positive load and 4.25" from original plane at 100% Negative load. At the completion of cycles the door panel was operable. There were no tears in the film. In our opinion, the tape and film used to seal for air leakage did not influence the results of the test.

Jarrett Wright and James Hayhurst, Test Technicians

Mfg Observers – Joe Zammitt



## IMPACT AND CYCLING TESTS (TAS 201/203)

### Specimen 8 – 180.0" x 120.0" Aluminum Sliding Glass Door (OOX)

#### TAS 201 and 203 – Large Missile Impact (2 x 4 Southern Yellow Pine)

Cond. Temp Of Specimen	Missile Level	Missile Weight	Missile Length	Muzzle Distance From Specimen
75°F	D	9.0 lbs, 3 oz	8'-0"	17'0"

Impact Location	Results	X - Measurement	Y - Measurement	Speed
1	Pass	59.00"	60.00"	50.1 fps
2	Pass	168.00"	11.00"	50.1 fps
3	Pass	146.00"	62.00"	49.9 fps
Orientation of Missile at Impact was within +/-5° of horizontal. None of the impacts penetrated the specimens. "X" measurement is from the left edge of test specimen. "Y" measurement is from the bottom edge of test specimen.				

#### TAS 201 and 203– Fatigue Load Cycling      Design Pressure +35.0 psf / -35.0 psf

Positive % of Test Load	Positive Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
20% to 50%	7.0 to 17.5	3500	1.76
0% to 60%	0.0 to 21.0	300	2.64
50% to 80%	17.5 to 28.0	600	1.28
30% to 100%*	10.5 to 35.0	100	2.51

Negative % of Test Load	Negative Pressure Range (psf)	Number Of Cycles	Average Cycle Time (Sec)
30% to 100%*	10.5 to 35.0	50	2.37
50% to 80%	17.5 to 28.0	1050	1.42
0% to 60%	0.0 to 21.0	50	2.49
20% to 50%	7.0 to 17.5	3350	1.72
*Panel deflected 2.13" from original plane at 100% Positive load and 2.50" from original plane at 100% Negative load. At the completion of cycles the door panel was operable. There were no tears in the film. In our opinion, the tape and film used to seal for air leakage did not influence the results of the test.			

Jarrett Wright and James Hayhurst, Test Technicians

Mfg Observers – Joe Zammitt

## Conditions, Terms, and General Notes Regarding These Tests

The product tested Has Been compared to the detailed drawing, bill of materials and fabrication information supplied by the client so named herein. Our analysis, which includes dimensional and component description comparisons, indicate the tested product and engineering information supplied by the client "Are Equivalent". The report and representative samples will be retained for four years from the date of initial test.

These test results were obtained by employing all requirements of the designated test methods with no Deviations unless explicitly noted in test report. The test results and specimen supplied for testing are in compliance with the reference.

The test results are specific to the product tested by this laboratory and of the sample supplied by the client named herein, and they relate to no other product either manufactured by the client, a fabricator of the client or of the client or of installed field performance.

This test report does not constitute certification of this product, but only that the above test results were obtained using the designated test methods and they indicate compliance with the performance requirements (paragraphs as listed) of the above referenced specifications.

Testing Evaluation Laboratories, Inc. makes no opinions or endorsements regarding this product and its performance. This report may not be reproduced or quoted in partial form without the expressed written approval of Testing Evaluation Laboratories, Inc.


Testing Evaluation Laboratories, Inc.'s letter, reports, its name or insignia or mark are for the exclusive use of the client so named herein and any other use is strictly prohibited. The report, letters and the name of Testing Evaluation Laboratories, Inc., its seal or mark shall not be used in any circumstance to the general public or in any advertising.

Limitation of liability: Due diligence was used in performing the tests and reporting the results. By acceptance of this report, this client agrees to hold harmless and indemnify Testing Evaluation Laboratories, Inc., its employees, sub-contractors, officers and owners against all claims and demands of any kind whatsoever, which arise out of or in any manner connected with the performance of work referred to herein.

Testing Evaluation Laboratories, Inc.



Vivian K. Wright,  
President



William B. Shelton, P.E.  
Florida P.E. # 26686

**Revision Log**

Rev No.	Date	Page(s)	Revision(s)
0	3/21/2014	NA	Original Report Issue

**TABLE OF CONTENTS**

SHEET #	DESCRIPTION
1	Table of contents
2	Test elevation
3	Horizontal cross sections
4	Vertical cross sections
5	Sill meeting stile block details
6	Frame anchoring
7	Components
8	Components and glazing detail
9	Bill of materials

Testing Evaluation Laboratories Inc  
Specimen Complies with Drawing  
Deviations Noted. TEL # 0199 1012  
Date 5/21/14 verified by *mtl*

*RW* BUILDING  
CONSULTANTS, INC.  
813.659.9197

DATE: 1/21/14

SCALE: N.T.S.


DWG. BY: JK

CHK. BY: LFS

DRAWING NO.:  
L-7113


SHEET 1 of 9

PRODUCT: FLEETWOOD GLACIER 3300 (OXX0)			
PART OR ASSEMBLY: TABLE OF CONTENTS			
NO.	DATE	BY	REVISIONS




Testing Evaluation Laboratories Inc  
 Specimen Coraplics with Drawing  
 Deviations Noted. TEL # 01991012  
 Date 3/21/14 verified by YLCC


PRODUCT:		FLEETWOOD GLACIER 3300 (OXX0)	
PART OR ASSEMBLY:		TEST ELEVATION	
NO.	DATE	REVISIONS	BY
DATE: 1/21/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7113			
SHEET 2 OF 9			



**1**  
**3** HORIZONTAL CROSS SECTION



**2**  
**3** HORIZONTAL CROSS SECTION




**3**  
**3** HORIZONTAL CROSS SECTION


NOTE:  
1. Item #J located six inches from each end then 12" o.c.

Testing Evaluation Laboratories Inc  
Specimen Complies with Drawing  
Deviations Noted TEL # 0199.1012  
Date 3/11/14 Verified by *www*

PRODUCT: FLEETWOOD GLACIER 3300 (0XX0)		PART OR ASSEMBLY: HORIZONTAL CROSS SECTIONS	
NO.	DATE	REVISIONS	BY
<div style="border: 1px solid black; padding: 5px; text-align: center;"> <b>RW</b> BUILDING CONSULTANTS, INC. 813.659.9197         </div>			
DATE: 1/21/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7113			
SHEET 3 OF 9			




**1**  
**4** VERTICAL CROSS SECTION



**2**  
**4** VERTICAL CROSS SECTION

Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted: TEL # 019991912  
 Date 3/21/14 Verified by Jillee


PRODUCT:		FLEETWOOD GLACIER 3300 (OXXO)	
PART OR ASSEMBLY:		VERTICAL CROSS SECTIONS	
NO.	DATE	REVISIONS	BY
<div style="border: 1px solid black; padding: 5px; text-align: center;"> <b>RW</b> BUILDING          CONSULTANTS, INC.          813.659.9197       </div>			
DATE: 1/21/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.:			
L-7113			
SHEET 4 OF 9			



Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted TEL # 01999012  
 Date 3/11/14 Verified by *[Signature]*




PRODUCT:		FLEETWOOD GLACIER 3300 (OXX0)	
PART OR ASSEMBLY:		SILL MEETING STILE BLOCK DETAILS	
NO.	DATE	REVISIONS	BY
 <b>RW BUILDING CONSULTANTS, INC.</b> 813.659.9197			
DATE: 1/21/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7113			
SHEET 5 OF 9			






Testing (TYP) Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted. TEL # 813.659.9197  
 Date 3/11/14 Verified by *[Signature]*

**FRAME ANCHORING**  
 2X buck construction




PRODUCT: FLEETWOOD GLACIER 3300 (OXXO)		PART OR ASSEMBLY: FRAME ANCHORING	
NO.	DATE	REVISIONS	BY
<div style="border: 1px solid black; padding: 5px;"> <p><i>RW</i> BUILDING CONSULTANTS, INC. 813.659.9197</p> </div>			
DATE: 1/21/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7113			
SHEET 6 OF 9			







9 HP INTERLOCK




10 FIXED INTERLOCK



12 HP THERMAL ADAPTOR - DOUBLE WING




37 SILL PAN





G1 GLAZING DETAIL

Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted - TEL # 01991012  
 Date 3/21/14 Verified by *WJW*



35 SILL MEETING STILE BLOCK





31 FIXED INTERLOCK BLOCK

PRODUCT:		FLEETWOOD GLACIER 3300 (OXX0)	
PART OR ASSEMBLY:		COMPONENTS AND GLAZING DETAIL	
NO.	DATE	REVISIONS	BY
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7113			
SHEET 8 OF 9			










**1**  
**3** HORIZONTAL CROSS SECTION



**2**  
**3** HORIZONTAL CROSS SECTION


NOTE:  
1. Item # J located six inches from each end then 12" o.c.

Testing Evaluation Laboratories Inc  
Specimen Complies with Drawing  
Deviations Noted TEL # 0199 1012  
Date 3/21/14 Modified by wllw

PRODUCT: FLEETWOOD GLACIER 3300 (OXO)		PART OR ASSEMBLY: HORIZONTAL CROSS SECTIONS	
NO.	DATE	REVISIONS	BY
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.:			
L-7114			
SHEET 3 OF 9			










Testing Evaluation Laboratories Inc  
 Specimens Complies with Existing  
 Deviations Noted TEL # 0199 1012  
 Date 02/11/14 Verified by *WLD*

PRODUCT:		FLEETWOOD GLACIER 3300 (OXO)	
PART OR ASSEMBLY:		SILL MEETING STILE BLOCK DETAILS	
NO.	DATE	REVISIONS	BY
 <b>RW</b> BUILDING CONSULTANTS, INC. 813.659.9197			
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.:			
L-7114			
SHEET 5 OF 9			




Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviation Note - TEL # 0199 1012  
 Date *5/11/14* verified by *Wiley*


SEE DETAIL 2      **FRAME ANCHORING**  
 2X buck construction      SEE DETAIL 1




**DETAIL 3**




**DETAIL 2**




**DETAIL 1**


PRODUCT: FLEETWOOD GLACIER 3300 (OXO)	
PART OR ASSEMBLY: FRAME ANCHORING	
NO.	BY
DATE	REVISIONS
 RW BUILDING CONSULTANTS, INC. 813.659.9197	
DATE: 2/24/14	
SCALE: N.T.S.	
DWG. BY: JK	
CHK. BY: LFS	
DRAWING NO.: L-7114	
SHEET 6 OF 9	




1 HEAD W/ NAIL FIN




3 JAMB W/ NAIL FIN




5 FIXED STILE



2 SILL




4 LOCK STILE




6 TOP RAIL


Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted: TEL # 0199 1012  
 Date 3/21/14 verified by *WJW*




18 TRACK



11 HEAD CHANNEL FILLER




7 SLIDING BOTTOM RAIL




8 FIXED BOTTOM RAIL


PRODUCT:		FLEETWOOD GLACIER 3300 (OXO)	
PART OR ASSEMBLY:		COMPONENTS	
NO.	DATE	REVISIONS	BY
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7114			
SHEET 7 OF 9			




9 HP INTERLOCK




10 FIXED INTERLOCK



12 FALL JAMB



27 SPACER  
Archetype Narrow Latch



G1 GLAZING DETAIL


Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted - TEL # 01991012  
 Date 3/21/14 Verified by *WJW*

PRODUCT: FLEETWOOD GLACIER 3300 (OXO)		PART OR ASSEMBLY: COMPONENTS AND GLAZING DETAIL	
NO.	DATE	REVISIONS	BY
RW BUILDING CONSULTANTS, INC. 813.659.9197			
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7114			
SHEET 8 OF 9			


**BILL OF MATERIALS**

ITEM #	DESCRIPTION	MATERIAL
B	2X BUCK SG >= 0.42	WOOD
C	1/4" MAX. SHIM SPACE	-
F	#10 X 2" PPH SMS	STEEL
G	#10 X 2-1/2" PPH SMS	STEEL
H	#10 X 1" PFH SMS	STEEL
J	#8 X 3/4" PPH SELF-DRILLING SMS	STEEL
K	#10 X 3" PFH WS	STEEL
L	1/4-20 - 1/2" MACHINE SCREW	STEEL
1	HEAD W/ NAIL FIN	6063-T6 ALUM
2	SILL	6063-T6 ALUM
3	JAMB W/ NAIL FIN	6063-T6 ALUM
4	LOCK STILE	6063-T6 ALUM
5	FIXED STILE	6063-T6 ALUM
6	TOP RAIL	6063-T6 ALUM
7	SLIDING BOTTOM RAIL	6063-T6 ALUM
8	FIXED BOTTOM RAIL	6063-T6 ALUM
9	HP INTERLOCK	6063-T6 ALUM
10	FIXED INTERLOCK	6063-T6 ALUM
11	HEAD CLOSER	6063-T6 ALUM
12	FALL JAMB	6063-T6 ALUM
13	SLIDING BOTTOM RAIL WEATHER STRIP	-
14	LOCK STILE SPREADER	6063-T6 ALUM
15	BOTTOM RAIL SPREADER	6063-T6 ALUM
16	TOP RAIL ISOLATOR	6063-T6 ALUM
17	ISOLATOR	6063-T6 ALUM
18	S.S. TRACK	SS
19	2 FINGER VINYL	-
20	SMALL FINSEAL	-
21	LARGE FINSEAL	-
22	GLAZING VINYL 1" SCR-900, 80 DUROMETER	-
23	SILL ISOLATOR	6063-T6 ALUM
24	ROLLER ASSEMBLY	-
25	STRIKE PLATE ASSY.(JAMB)	-
26	LATCH ASSY.(JAMB)(Archetype Narrow Latch)	-
27	SPACER (ARCHETYPE NARROW LATCH)	-
32	3" X 4" L-BRACKETT	6063-T6 ALUM

Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted - TEL # 01991012  
 Date: 3/11/14 Verified by: *mlw*

PRODUCT: FLEETWOOD GLACIER 3300 (OXO)	PART OR ASSEMBLY: BILL OF MATERIALS	
		REVISIONS NO. DATE BY
 RW BUILDING CONSULTANTS, INC. 813.659.9197		
DATE: 2/24/14		
SCALE: N.T.S.		
DWG. BY: JK		
CHK. BY: LFS		
DRAWING NO.: L-7114		
SHEET 9 OF 9		







Testing Evaluation Laboratories Inc  
Specimen Complies with Drawing  
Deviations Noted - TEL #01991012  
Date 3/21/14 Verified by *[Signature]*


PRODUCT: FLEETWOOD GLACIER 3300 (00X)	
PART OR ASSEMBLY: TEST ELEVATION	
NO.	REVISIONS
DATE	BY

**RW** BUILDING  
CONSULTANTS, INC.  
813.659.9197

DATE: 2/24/14  
SCALE: N.T.S.  
DWG. BY: JK  
CHK. BY: LFS  
DRAWING NO.:  
L-7112  
SHEET 2 OF 9



**1**  
**3** HORIZONTAL CROSS SECTION




**2**  
**3** HORIZONTAL CROSS SECTION

NOTE:  
1. Item #J located six inches from each end then 12" o.c.


Testing Evaluation Laboratories Inc  
Specimen Complies with Drawing  
Deviation Noted TEL # 0199 1912  
Date 3/11/14 certified by *[Signature]*

PRODUCT: FLEETWOOD GLACIER 3300 (00X)		PART OR ASSEMBLY: HORIZONTAL CROSS SECTIONS	
NO.	DATE	REVISIONS	BY
 RW BUILDING CONSULTANTS, INC. 813.659.9197			
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7112			
SHEET 3 OF 9			






**1**  
**4** VERTICAL CROSS SECTION



**2**  
**4** VERTICAL CROSS SECTION



Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted TEL # 01991012  
 Date 3/21/14 Verified by *[Signature]*

PRODUCT: FLEETWOOD GLACIER 3300 (00X)		PART OR ASSEMBLY: VERTICAL CROSS SECTIONS	
NO.	DATE	REVISIONS	BY
<div style="border: 1px solid black; padding: 5px;"> <p><b>RW</b> BUILDING CONSULTANTS, INC. 813.659.9197</p> </div>			
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7112			
SHEET 4 OF 9			



Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted TEL # 01991012  
 Date 3/21/14 Verified by JLL


PRODUCT:		FLEETWOOD GLACIER 3300 (00X)	
PART OR ASSEMBLY:		SILL MEETING STILE BLOCK DETAILS	
NO.	DATE	BY	REVISIONS
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7112			
SHEET 5 OF 9			




Testing Evaluation Laboratories Inc  
 Specimens Complies with Drawing  
 Deviations Noted TEL # 01991012  
 Date 3/11/14 Verified by *[Signature]*

SEE DETAIL 2 **FRAME ANCHORING** 2X buck construction SEE DETAIL 1


**LOCK JAMB**



**DETAIL 3**




**DETAIL 2**




**DETAIL 1**


PRODUCT: FLEETWOOD GLACIER 3300 (00X)		PART OR ASSEMBLY: FRAME ANCHORING	
NO.	DATE	BY	REVISIONS
 RW BUILDING CONSULTANTS, INC. 813.659.9197			
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7112			
SHEET 6 OF 9			




1 HEAD W/ NAIL FIN




3 JAMB W/ NAIL FIN




5 FIXED STILE



2 SILL




4 LOCK STILE




6 TOP RAIL


Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Noted - TEL # 01991012  
 Date 3/21/14 Verified by *[Signature]*




18 TRACK



11 HEAD CHANNEL FILLER




7 SLIDING BOTTOM RAIL




8 FIXED BOTTOM RAIL


PRODUCT: FLEETWOOD GLACIER 3300 (00X)		PART OR ASSEMBLY: COMPONENTS	
NO.	DATE	REVISIONS	BY
 RW BUILDING CONSULTANTS, INC. 813.659.9197			
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7112			
SHEET 7 OF 9			




9 HP INTERLOCK



10 FIXED INTERLOCK



12 FALL JAMB



G1 GLAZING DETAIL

Testing Evaluation Laboratories Inc  
 Specimen Complies with Drawing  
 Deviations Notes - TEL # 01991010  
 Date 3/11/14 Verified by [Signature]

PRODUCT:		FLEETWOOD GLACIER 3300 (00X)	
PART OR ASSEMBLY:		COMPONENTS AND GLAZING DETAIL	
NO.	DATE	BY	REVISIONS
<div style="border: 1px solid black; padding: 5px; text-align: center;"> <p><b>RW</b> BUILDING CONSULTANTS, INC. 813.659.9197</p> </div>			
DATE: 2/24/14			
SCALE: N.T.S.			
DWG. BY: JK			
CHK. BY: LFS			
DRAWING NO.: L-7112			
SHEET 8 OF 9			

**BILL OF MATERIALS**

ITEM #	DESCRIPTION	MATERIAL
B	2X BUCK SG >= 0.42	WOOD
C	1/4" MAX. SHIM SPACE	-
F	#10 X 2" PPH SMS	STEEL
G	#10 X 2-1/2" PPH SMS	STEEL
H	#10 X 1" PFH SMS	STEEL
J	#8 X 3/4" PPH SELF-DRILLING SMS	STEEL
K	#10 X 3" PFH WS	STEEL
L	1/4-20 - 1/2" MACHINE SCREW	STEEL
1	HEAD W/ NAIL FIN	6063-T6 ALUM
2	SILL	6063-T6 ALUM
3	JAMB W/ NAIL FIN	6063-T6 ALUM
4	LOCK STILE	6063-T6 ALUM
5	FIXED STILE	6063-T6 ALUM
6	TOP RAIL	6063-T6 ALUM
7	SLIDING BOTTOM RAIL	6063-T6 ALUM
8	FIXED BOTTOM RAIL	6063-T6 ALUM
9	HP INTERLOCK	6063-T6 ALUM
10	FIXED INTERLOCK	6063-T6 ALUM
11	HEAD CLOSER	6063-T6 ALUM
12	FALL JAMB	6063-T6 ALUM
13	SLIDING BOTTOM RAIL WEATHER STRIP	-
14	LOCK STILE SPREADER	6063-T6 ALUM
15	BOTTOM RAIL SPREADER	6063-T6 ALUM
16	TOP RAIL ISOLATOR	6063-T6 ALUM
17	ISOLATOR	6063-T6 ALUM
18	S.S. TRACK	SS
19	2 FINGER VINYL	-
20	SMALL FINSEAL	-
21	LARGE FINSEAL	-
22	GLAZING VINYL 1" SCR-900, 80 DUROMETER	-
23	SILL ISOLATOR	6063-T6 ALUM
24	ROLLER ASSEMBLY	-
25	STRIKE PLATE ASSY.(JAMB)	-
26	LATCH ASSY.(JAMB)	-
32	3" X 4" L-BRACKETT	6063-T6 ALUM

Testing Evaluation Laboratories Inc  
Specimen Complies with Drawing  
Deviations Noted TEL # 01991012  
Date 3/21/14 Verified by *[Signature]*

PRODUCT:		FLEETWOOD GLACIER 3300 (00X)
PART OR ASSEMBLY:		BILL OF MATERIALS
NO.		DATE
BY		REVISIONS
DATE: 2/24/14		
SCALE: N.T.S.		
DWG. BY: JK		
CHK. BY: LFS		
DRAWING NO.: L-7112		
SHEET 9 OF 9		